

Attestation of Conformity

No. E8AUK 089086 0185 Rev. 01


Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Power supplies**
(Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Electromagnetic Compatibility Regulations 2016 relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 657402105402

Date, 2022-09-17



(Laurent Yuan)

Attestation of Conformity

No. E8AUK 089086 0185 Rev. 01

Model(s):

**BK-BEL009-AXXXA; BK-BEL013-AXXXA;
BK-BEL009-BXXXXA; BK-BEL013-BXXXXA;
BK-BEL018-AXXXA; BK-BEL022-AXXXA;
BK-BEL040-BXXXXA; BK-BEL040-CXXXXA;
BK-BEL042-AXXXA; BK-BEL050-AXXXA;
BK-BEL060-AXXXA; BK-BLL040-AXXXA
(‘XXXX’=0120-1650 indicates rated output
current (I_{rated}) 0.12-1.65A, in steps of 0.01A)**

**Description of
Object:**

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection Class: II

**Tested
according to:**

EN IEC 55015:2019/A11:2020
EN IEC 61000-3-2:2019/A1:2021
EN 61000-3-3:2013/A2:2021
EN 61547:2009

Attestation of Conformity

No. E8AUK 089086 0185 Rev. 01

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W) Max.
BK-BEL009-AXXXXA	0.07	28-42	120-250	50	10.5
BK-BEL013-AXXXXA	0.09	28-42	250-300	50	12.6
		28-40	310-350		14.0
BK-BEL009-BXXXXA	0.07	30-42	120-250	50	10.5
BK-BEL013-BXXXXA	0.08	30-42	250-300	50	12.6
		30-40	310-350		14.0
BK-BEL018-AXXXXA	0.11	28-42	250-400	50	16.8
		28-40	410-450		18
BK-BEL022-AXXXXA	0.14	28-42	350-500	50	21
		28-40	510-550		22
		28-38	560-600		22.8
BK-BEL040-BXXXXA	0.24	30-42	500-950	50	39.9
		30-40	960-1000		40
BK-BEL040-CXXXXA	0.24	30-42	500-950	50	39.9
		30-40	960-1000		40
BK-BEL042-AXXXXA	0.25	28-42	800-1000	50	42
		28-40	1010-1050		42
		28-38	1060-1100		41.8
BK-BEL050-AXXXXA	0.29	28-42	1000-1200	50	50.4
		28-40	1210-1250		50
BK-BEL060-AXXXXA	0.38	28-42	1200-1500	50	63
		28-40	1510-1550		62
		28-38	1560-1650		62.7
BK-BLL040-AXXXXA	0.24	30-42	500-950	50	39.9
		30-40	960-1000		40