

CERTIFICATE

No. U6 089086 0236 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Constant Voltage LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215025901

Date, 2022-09-28



(Taylor Yao)

CERTIFICATE

No. U6 089086 0236 Rev. 00

Model(s):

BK-DGV036-24V0d; BK-DGV036-24V0dP;
BK-DGV036-24V0D; BK-DGV036-24V0DP;
BK-DGV036-48V0d; BK-DGV036-48V0dP;
BK-DGV036-48V0D; BK-DGV036-48V0DP;
BK-DGV060-24V0d; BK-DGV060-24V0dP;
BK-DGV060-24V0D; BK-DGV060-24V0DP;
BK-DGV060-48V0d; BK-DGV060-48V0dP;
BK-DGV060-48V0D; BK-DGV060-48V0DP;
BK-DGV100-24V0d; BK-DGV100-24V0dP;
BK-DGV100-24V0D; BK-DGV100-24V0DP;
BK-DGV100-48V0d; BK-DGV100-48V0dP;
BK-DGV100-48V0D; BK-DGV100-48V0DP;
BK-DGV150-24V0d; BK-DGV150-24V0dP;
BK-DGV150-24V0D; BK-DGV150-24V0DP;
BK-DGV150-48V0d; BK-DGV150-48V0dP;
BK-DGV150-48V0D; BK-DGV150-48V0DP;
BK-DGV200-24V0d; BK-DGV200-24V0dP;
BK-DGV200-24V0D; BK-DGV200-24V0DP;
BK-DGV200-48V0d; BK-DGV200-48V0dP;
BK-DGV200-48V0D; BK-DGV200-48V0DP

Brand Name:

BOKE

**Parameters:**

Rated Input Voltage: 200-240VAC
Rated Frequency: 50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class I (with endcap); SELV
Degree of Protection: IP20 (with endcap)
Method of Installation: Independent (with endcap);
Built-in (without endcap)
Type of Output: Constant voltage type
ta: 60°C
tc: See below table for details

**Tested
according to:**

EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

**Production
Facility(ies):**

089086

CERTIFICATE

No. U6 089086 0236 Rev. 00

Model	Rated Input Current (A) Max.	U _{rated} (VDC)	Output Current (A)	P _{rated} (W) Max.	tc (°C)
BK-DGV036-24V0d, BK-DGV036-24V0dP, BK-DGV036-24V0D, BK-DGV036-24V0DP	0.25	24	1.5	36.0	90
BK-DGV036-48V0d, BK-DGV036-48V0dP, BK-DGV036-48V0D, BK-DGV036-48V0DP	0.25	48	0.75	36.0	90
BK-DGV060-24V0d, BK-DGV060-24V0dP, BK-DGV060-24V0D, BK-DGV060-24V0DP	0.35	24	2.5	60.0	90
BK-DGV060-48V0d, BK-DGV060-48V0dP, BK-DGV060-48V0D, BK-DGV060-48V0DP	0.35	48	1.2	57.6	90
BK-DGV100-24V0d, BK-DGV100-24V0dP, BK-DGV100-24V0D, BK-DGV100-24V0DP	0.65	24	4.2	100.0	95
BK-DGV100-48V0d, BK-DGV100-48V0dP, BK-DGV100-48V0D, BK-DGV100-48V0DP	0.65	48	2.09	100.0	95
BK-DGV150-24V0d, BK-DGV150-24V0dP, BK-DGV150-24V0D, BK-DGV150-24V0DP	1.0	24	6.25	150.0	90
BK-DGV150-48V0d, BK-DGV150-48V0dP, BK-DGV150-48V0D, BK-DGV150-48V0DP	1.0	48	3.12	150.0	90
BK-DGV200-24V0d, BK-DGV200-24V0dP, BK-DGV200-24V0D, BK-DGV200-24V0DP	1.1	24	8.3	199.2	90
BK-DGV200-48V0d, BK-DGV200-48V0dP, BK-DGV200-48V0D, BK-DGV200-48V0DP	1.1	48	4.15	199.2	90