

CERTIFICATE

No. U6 089086 0424 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Constant Current LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142225000702

Date, 2023-11-02



(Taylor Yao)

CERTIFICATE

No. U6 089086 0424 Rev. 00

Model(s):

BK-DDL030-0800Ad; BK-DDL030-0800ADP;
BK-DDL030-0800ADF; BK-DDL042-0800Bd;
BK-DDL042-0800BDP; BK-DDL042-0800BDF;
BK-DDL042-1100Ad; BK-DDL042-1100ADP;
BK-DDL042-1100ADF; BK-DKL022-A0600AD;
BK-DKL022-A0600ADP; BK-DKL022-A0600ADF;
BK-DKL022-AxxxxADN; BK-DKL040-A1050AD;
BK-DKL040-A1050ADP; BK-DKL040-A1050ADF;
BK-DKL040-AxxxxADN
(‘xxxx’=0225-1050 indicates rated output current
(I_{rated}) 225-1050mA, in steps of 1mA)

Brand Name:

BOKE

**Parameters:**

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant current type
ta: 45°C
tc: See below table for details

**Tested
according to:**

EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

**Production
Facility(ies):**

089086

CERTIFICATE

No. U6 089086 0424 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)	tc (°C)
BK-DDL030-0800Ad; BK-DDL030-0800ADP; BK-DDL030-0800ADF	0.18	6-42	250	50	10.50	85
		6-42	275		11.55	
		6-42	300		12.60	
		6-42	325		13.65	
		6-42	350		14.70	
		6-42	375		15.75	
		6-42	400		16.80	
		6-42	425		17.85	
		6-42	450		18.90	
		6-42	500		21.00	
		6-42	550		23.10	
		6-42	600		25.20	
		6-42	650		27.30	
		6-42	700		29.40	
		6-40	750		30.00	
		6-38	800		30.40	
BK-DDL042-0800Bd; BK-DDL042-0800BDP; BK-DDL042-0800BDF	0.25	6-84	250	100	21.00	85
		6-84	275		23.10	
		6-84	300		25.20	
		6-84	325		27.30	
		6-84	350		29.40	
		6-84	375		31.50	
		6-84	400		33.60	
		6-84	425		35.70	
		6-84	450		37.80	
		6-84	500		42.00	
		6-76	550		41.80	
		6-70	600		42.00	
		6-64	650		41.60	
		6-60	700		42.00	
		6-56	750		42.00	
		6-52	800		41.60	
BK-DDL042-1100Ad; BK-DDL042-1100ADP; BK-DDL042-1100ADF	0.25	6-42	450	50	18.90	85
		6-42	475		19.95	
		6-42	500		21.00	
		6-42	525		22.05	
		6-42	550		23.10	
		6-42	600		25.20	
		6-42	650		27.30	
		6-42	700		29.40	
		6-42	750		31.50	
		6-42	800		33.60	
		6-42	850		35.70	
		6-42	900		37.80	
		6-42	950		39.90	
		6-42	1000		42.00	
		6-40	1050		42.00	
		6-38	1100		41.80	

CERTIFICATE

No. U6 089086 0424 Rev. 00

BK-DKL022-A0600AD; BK-DKL022-A0600ADP; BK-DKL022-A0600ADF	0.14	24-42	225	50	9.45	90
		24-42	250		10.50	
		24-42	275		11.55	
		24-42	300		12.60	
		24-42	350		14.70	
		24-42	400		16.80	
		24-42	450		18.90	
		24-42	500		21.00	
		24-40	550		22.00	
		24-38	600		22.80	
BK-DKL022-AxxxxADN	0.14	24-42	225-600	50	22.80	90
BK-DKL040-A1050AD; BK-DKL040-A1050ADP; BK-DKL040-A1050ADF	0.23	24-42	600	50	25.2	90
		24-42	650		27.3	
		24-42	700		29.4	
		24-42	750		31.5	
		24-42	800		33.6	
		24-42	850		35.7	
		24-42	900		37.8	
		24-42	950		39.9	
		24-40	1000		40.0	
		24-38	1050		39.9	
BK-DKL040-AxxxxADN	0.23	24-42	600-1050	50	40.0	90