

CERTIFICATE

No. U6 089086 0443 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Constant Current LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142235039601

Date, 2024-02-02



(Taylor Yao)

CERTIFICATE

No. U6 089086 0443 Rev. 00

Model(s): BK-SWL022-A0350AS; BK-SWL022-A0600AS;
BK-SWL022-AxxxxAR; BK-SWL040-A0800AS;
BK-SWL040-A1050AS; BK-SWL040-AxxxxAR;
BK-SWL060-A1150AS; BK-SWL060-A1400AS;
BK-SWL060-A1650AS; BK-SWL060-AxxxxAR
(xxxx=0150-1650 indicates rated output current
(I_{rated}) 150-1650mA, in steps of 1mA)

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC

Rated Frequency: 0/50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class I (with endcap); SELV

Degree of Protection: IP20 (with endcap)

Method of Installation: Independent (with endcap);

Built-in (without endcap)

Type of Output: Constant current type

ta: 60°C

tc: 90°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0443 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	P _{rated} (W) Max.	U _{out} (VDC)
BK-SWL022-A0350AS	0.135	24-42	150	6.3	60
			200	8.4	
			250	10.5	
			300	12.6	
			350	14.7	
BK-SWL022-A0600AS	0.135	24-42	400	16.8	60
		24-42	450	18.9	
		24-42	500	21.0	
		24-40	550	22.0	
		24-38	600	22.8	
BK-SWL022-AxxxxAR	0.135	24-42	150-350	14.7	60
		24-42	360-500	21.0	
		24-40	510-550	22.0	
		24-38	560-600	22.8	
BK-SWL040-A0800AS	0.23	24-42	600	25.2	50
			650	27.3	
			700	29.4	
			750	31.5	
BK-SWL040-A1050AS	0.23	24-42	850	35.7	50
		24-42	900	37.8	
		24-42	950	39.9	
		24-40	1000	40.0	
BK-SWL040-AxxxxAR	0.23	24-38	1050	39.9	50
		24-42	600-800	33.6	
		24-42	810-950	39.9	
		24-40	960-1000	40.0	
BK-SWL060-A1150AS	0.4	24-42	1010-1050	39.9	60
			950	39.9	
			1000	42.0	
			1050	44.1	
BK-SWL060-A1400AS	0.4	24-42	1100	46.2	60
			1150	48.3	
			1200	50.4	
			1250	52.5	
BK-SWL060-A1650AS	0.4	24-42	1300	54.6	60
		24-42	1350	56.7	
		24-42	1400	58.8	
		24-42	1450	60.9	
BK-SWL060-AxxxxAR	0.4	24-40	1500	63.0	60
		24-38	1550	62.0	
		24-38	1600	60.8	
		24-38	1650	62.7	
BK-SWL060-AxxxxAR	0.4	24-42	950-1150	48.3	60
		24-42	1160-1400	58.8	
		24-42	1410-1500	63.0	
		24-40	1510-1550	62.0	
BK-SWL060-AxxxxAR	0.4	24-38	1560-1650	62.7	60
		24-38	1560-1650	62.7	
		24-38	1560-1650	62.7	
		24-38	1560-1650	62.7	