

CERTIFICATE

No. U6 089086 0725 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Electronic controlgear for LED modules
(LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142255030801

Date, 2026-03-26



(Taylor Yao)

CERTIFICATE

No. U6 089086 0725 Rev. 00

Model(s):

BK-PBL060S-A1650AS; BK-PBL060S-A1650ASE;
BK-PBL060S-A1650ASC; BK-PBL060S-A1650ASEC;
BK-PBL060S-AXXXXAS; BK-PBL060S-AXXXXASE;
BK-PBL060S-AXXXXASC; BK-PBL060S-AXXXXASEC;
BK-PBL013S-B0350AS; BK-PBL013S-B0350ASE;
BK-PBL013S-BXXXXAS; BK-PBL013S-BXXXXASE;
BK-PBL022S-B0600AS; BK-PBL022S-B0600ASE;
BK-PBL022S-BXXXXAS; BK-PBL022S-BXXXXASE;
BK-PBL022E-B0600AS; BK-PBL022E-B0600ASE;
BK-PBL022E-BXXXXAS; BK-PBL022E-BXXXXASE;
BK-PBL010E-B0350BS; BK-PBL010E-B0350BSE;
BK-PBL010E-BXXXXBS; BK-PBL010E-BXXXXBSE;
BK-PBL013E-B0500BS; BK-PBL013E-B0500BSE;
BK-PBL013E-BXXXXBS; BK-PBL013E-BXXXXBSE;
BK-DWL010S-BHA0700ADP; BK-DWL010S-BHA0700ADN;
BK-DWL010S-BHAXXXXADP; BK-DWL010S-BHAXXXXADN;
BK-DCL022S-AHA1050ADP; BK-DCL022S-AHA1050ADN;
BK-DCL022S-AHAXXXXADP; BK-DCL022S-AHAXXXXADN;
BK-BSL022-AXXXXA

('XXXX'=0100-1640 indicates rated output current (I_{rated}) 100-1640mA)

Brand Name:

BOKE

**Parameters:**

Rated Input Voltage: 200-240VAC/DC (for models with suffix BSE, ASE, ASEC, ADP, ADN)

200-240VAC (for all other models)

Rated Frequency: 0/50/60Hz (for models with suffix BSE, ASE, ASEC, ADP, ADN)

50/60Hz (for all other models)

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant current type

ta: See below table for details

tc: See below table for details

Tested**according to:**

EN IEC 61347-2-13:2024

EN IEC 61347-1:2024

EN IEC 62384:2020

Production**Facility(ies):**

089086

CERTIFICATE

No. U6 089086 0725 Rev. 00

Series	Model	Rated Input Current (A) Max.	P _{rated} (W) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	ta (°C)	tc (°C)
1	BK-PBL060S-A1650AS BK-PBL060S-A1650ASE BK-PBL060S-A1650ASC BK-PBL060S-A1650ASEC	0.38	37.80	28-42	900	54	45	85
			39.90	28-42	950			
			42.00	28-42	1000			
			44.10	28-42	1050			
			46.20	28-42	1100			
			48.30	28-42	1150			
			50.40	28-42	1200			
			52.50	28-42	1250			
			54.60	28-42	1300			
			56.70	28-42	1350			
			58.80	28-42	1400			
			60.90	28-42	1450			
			63.00	28-42	1500			
2	BK-PBL013S-B0350AS BK-PBL013S-B0350ASE	0.077	4.20	28-42	100	50	60	80
			6.30	28-42	150			
			8.40	28-42	200			
			10.50	28-42	250			
			12.60	28-42	300			
2	BK-PBL013S-B0600AS BK-PBL013S-B0600ASE	0.13	12.60	28-42	300	50	50 (Io>500mA) 60 (Io≤500mA)	80
			14.70	28-42	350			
			16.80	28-42	400			
			18.90	28-42	450			
			21.00	28-42	500			
2	BK-PBL022S-BXXXXAS BK-PBL022S-BXXXXASE	0.13	22.00	28-40	550	50	50 (Io>500mA) 60 (Io≤500mA)	80
			22.80	28-38	600			
			8.40	28-42	200-590			
			12.60	28-42	300			
			14.70	28-42	350			
3	BK-PBL022E-B0600AS BK-PBL022E-B0600ASE	0.14	16.80	28-42	400	50	50	90
			18.90	28-42	450			
			21.00	28-42	500			
			22.00	28-40	550			
			22.80	28-38	600			
4	BK-PBL010E-B0350BS BK-PBL010E-B0350BSE	0.05	4.40	15-22	200	35	60	90
			5.50	15-22	250			

CERTIFICATE

No. U6 089086 0725 Rev. 00

			6.60	15-22	300			
			7.70	15-22	350			
4	BK-PBL010E-BXXXXBS BK-PBL010E-BXXXXBSE	0.05	2.20-7.48	15-22	100-340	35	60	90
4	BK-PBL013E-B0500BS BK-PBL013E-B0500BSE	0.065	7.70	15-22	350	35	60	90
			8.80	15-22	400			
			9.90	15-22	450			
			11.00	15-22	500			
4	BK-PBL013E-BXXXXBS BK-PBL013E-BXXXXBSE	0.065	4.40-10.78	15-22	200-490	35	60	90
5	BK-DWL010S-BHA0700ADP	0.08	4.20	2.5-42	100	50	50 (Po≤10.5W, Io≤700mA) 60 (Po≤9W, Io≤600mA)	90
			5.25	2.5-42	125			
			6.30	2.5-42	150			
			7.35	2.5-42	175			
			8.40	2.5-42	200			
			9.45	2.5-42	225			
			10.50	2.5-42	250			
			10.50	2.5-35	300			
			10.50	2.5-30	350			
			10.40	2.5-26	400			
			10.35	2.5-23	450			
			10.50	2.5-21	500			
			10.45	2.5-19	550			
			10.20	2.5-17	600			
			10.40	2.5-16	650			
			10.50	2.5-15	700			
5	BK-DWL010S-BHA0700ADN	0.08	10.50	2.5-42	100-700	50	50 (Po≤10.5W, Io≤700mA) 60 (Po≤9W, Io≤600mA)	90
5	BK-DWL010S-BHAXXXADP BK-DWL010S-BHAXXXADN	0.08	4.20-10.50	2.5-42	100-690	50	50 (Po≤10.5W, Io≤690mA) 60 (Po≤9W, Io≤600mA)	90
6	BK-DCL022S-AHA1050ADP	0.14	6.30	2.5-42	150	50	45	90
			10.50	2.5-42	250			
			14.70	2.5-42	350			
			18.90	2.5-42	450			
			21.00	2.5-42	500			
			22.00	2.5-40	550			
			22.80	2.5-38	600			
			22.75	2.5-35	650			
			22.40	2.5-32	700			
			22.50	2.5-30	750			
			22.40	2.5-28	800			
			22.10	2.5-26	850			
			21.60	2.5-24	900			
			21.80	2.5-23	950			
			22.00	2.5-22	1000			
			22.05	2.5-21	1050			
6	BK-DCL022S-AHA1050ADN	0.14	22.80	2.5-42	100-1050	50	45	90
6	BK-DCL022S-AHAXXXADP	0.14	4.20-22.80	2.5-42	100-1040	50	45	90



Product Service

CERTIFICATE

No. U6 089086 0725 Rev. 00

	BK-DCL022S-AHAXXXXADN							
7	BK-BSL022-AXXXXA	0.14	4.20-25.20	28-42	100-600	54	60	90